



TLK SERIES
TUNNEL TRUCK

To be the leading supplier of engineering transportation solution and equipment



Special equipment for ramp transportation in underground mining.

Strong power, high efficiency, high load capacity.

Optional IBS intelligent auxiliary brake control system, visual system, lifting alarm device, exhaust gas purification treatment device, etc., with safety, environmental protection characteristics.

TLK series tunnel truck				
Overall parameters	Model	TLK321	TLK361	TLK451
	Brand	Tonly	Tonly	Tonly
	Kerb weight (t)	12.5	13.8	15.5
	Rated payload (t)	20	25	30
	GVW (t)	32.5	38.8	45.5
	Dimensions (mm)	7600×2490×2590	7600×2610×2680	8500×2550×2760
	Wheel track (mm)	3600	1990/1850	4100
	Standard bucket volume (m³)	8.8	11.8	15
	Tire specification	10.00R20	12.00R20	12.00R20
	Rim specifications	7.5V-20	8.5V-20	8.5V-20
	Lifting system	Double cylinder mid-lift	Double cylinder mid-lift	Double cylinder mid-lift
	Max. speed (km/h)	40	40	40
	Maximum climbing degree (%)	30%	30%	30%
	Minimum turning radius (m)	20	21	22
	Minimum ground clearance (mm)	250	280	280
Engine	Axle (t)	Hande (6.5+16+16)	Hande (6.5+16+16)	Hande (9.5+16+16)
	Model	YC6L330-T300	YC6L330-T300	YCK09400-T300
	Manufacturer / Country	Yuchai/China	Yuchai/China	Yuchai/China
Transmission	Power (hp/kw)	330/243	330/243	400/294
	Model	7DS100	7DS100	7DS180
	Manufacturer / Country	Fast/China	Fast/China	Fast/China
Container	Transmission device	Direct manipulation	Direct manipulation	Direct manipulation
	Base plate material/thickness (mm)	NM400/12	NM400/12	NM400/12
	Rear plate material/thickness (mm)	NM400/8	NM400/8	NM400/8
	Front plate material/thickness (mm)	NM400/8	NM400/8	NM400/8
	Side plate material/thickness (mm)	NM400/8	NM400/8	NM400/8
	Container size (mm)	4500×2400×850	4500×2400×1100	4500×2400×1350
	Container volume (m³)	8.8	11.8	15